

TO	LR Zagreb	DATE	21 April 2017		
FROM	Materials and NDE	YOUR REF			
		OUR REF	MAT/M1391/GYE/		
SUBJECT	Scope of Approval ACRONI, d.o.o. Member of Slovenian Steel Group Cesta Borisa Kidrica 44 SI - 4270 Jesenice Slovenia				

MAKE OF APPROVED TESTING MACHINE	TYPE	MACHINE NUMBER	CAPACITY	UNIT
ZWICK/ROEL	Impact	16730	300	Joules
ZWICK	Tensile	332380	600	kN
ZWICK	Tensile	171877-2006	600	kN
ZWICK	Tensile	171245-2007	100	kN
MFL MANNHEIM	Impact	123	300	Joules

Steelmaking	E.A.F. / Con Cast	Grades	
		carbon, carbon-manganese	
Steelmaking	B.O.S/V.O.D./Con Cast	Grades	
		austenitic stainless	
Semi-Finished Products	Slabs	Grades	mm thickness Maximum
-	-	carbon, carbon-manganese, austenitic stainless	250.0
Plates	Normal Strength	Grades	mm thickness Maximum
As Rolled	Fine Grain Al	A, B	40.0
As Rolled	Killed	A	40.0
Normalized	Fine Grain Al	D, E	40.0
Plates	Higher Strength	Grades	mm thickness Maximum
Normalized	Fine Grain Al+Nb+V	AH27S, AH32, AH36, DH27S, DH32, DH36, EH27S, EH32, EH36	40.0
Plates	Boiler & Pressure Vessel	Grades	mm thickness Maximum
As Rolled	Killed	360AR, 410AR	40.0
Normalized	Fine Grain Al+Nb+V	360FG, 410FG, 460FG, 490FG, 510FG	40.0
Normalized	Fine Grain Al	360FG, 410FG	40.0
Normalized	Killed	360, 410	40.0
Plates	Austenitic Stainless	Grades	mm thickness Maximum
Solution Treated	-	304L, 316L, 317L, 321, 347	70.0

Slabs approved to maximum dimensions 250 x 2000mm

Austenitic stainless type 316Ti plates approved to 70mm thickness for approved applications only.